



# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 10/06/2023

Revision date: 04/04/2023

Version: 2.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Holcim Solutions and Products US, LLC  
26 Century Boulevard, Suite 205  
Nashville, Tennessee 37214  
1-800-878-7876 • www.holcimpacpoly.com

#### 1.4. Emergency telephone number

Emergency number : For Chemical Emergency  
Spill, Leak, Fire, Exposure, or Incident  
CHEMTREC:  
Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Respiratory sensitization, Category 1 H334  
Skin sensitization, Category 1 H317

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger  
Hazard statements (GHS US) : H317 - May cause an allergic skin reaction.  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Precautionary statements (GHS US) : P261 - Avoid breathing vapors/spray/mist.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves, eye protection, face protection, protective clothing  
P284 - In case of inadequate ventilation, wear respiratory protection.  
P302+P352 - If on skin: Wash with plenty of soap and water.  
P304+P341 - IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER, a doctor.  
P363 - Wash contaminated clothing before reuse.  
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 3.2. Mixtures

Name	Product identifier	%*
Isophorone diisocyanate	(CAS-No.) 4098-71-9	<0.5
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS-No.) 41556-26-7	0.1 – 1
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidyl ester	(CAS-No.) 82919-37-7	0.1 – 1

\* In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Get medical attention if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/effects after skin contact : May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Direct contact with eyes is likely to be irritating.
- Symptoms/effects after ingestion : May cause gastrointestinal irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Carbon dioxide. Foam. Dry powder. Water spray. Sand.
- Unsuitable extinguishing media : Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool.

### 5.2. Specific hazards arising from the chemical

- Fire hazard : Not flammable.
- Explosion hazard : Product is not explosive.
- Reactivity : Reacts with water.

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use cold water spray to cool fire-exposed containers to minimize risk of rupture. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment/cleaning up : SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep/shovel into opentop containers with lids for disposal. Do not pressurize the container. Wipe off traces of material. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Know and prepare for spill response before using or handling this product. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled containers for disposal. Use appropriate PPE. Place absorbent diking materials in covered containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### 6.4. Reference to other sections

See Sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation).

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place. Protect from moisture. Keep container tightly closed.

Maximum storage period : 6 – 9 months (unopened containers stored in cool dry locations)

Storage temperature : 15.5 – 29.4 °C (60 – 85 °F)

Special rules on packaging : Keep only in original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
<b>Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)</b>		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
<b>Isophorone diisocyanate (4098-71-9)</b>		
ACGIH	ACGIH OEL TWA [ppm]	0.005 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Resp sens
ACGIH	Regulatory reference	ACGIH 2020

# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ensure adequate ventilation, especially in confined areas.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment symbol(s):



#### Personal protective equipment:

Gloves. Protective goggles. Protective clothing. In case of inadequate ventilation, wear respiratory protection.

#### Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

#### Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to airborne particles.

#### Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

#### Respiratory protection:

Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where dust exceeds PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid mixture, self-leveling, glossy
Color	: White or Concrete Grey
Odor	: Mild
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C (212 °F)
Relative evaporation rate (n-butyl acetate=1)	: < 1
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 1
Relative density	: 1.13 – 1.16
Density	: 9.55 lb/gal ±0.2 lbs/gal
Solubility	: Reacts with water
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 6000 cP ±1000 cP, at 23.9 °C (75.0 °F)

# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive limits : No data available  
Explosive properties : No data available  
Oxidising properties : No data available

### 9.2. Other information

VOC content : 19 g/l EPA Method 24 VOC

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with water.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

High temperatures, incompatible materials.

### 10.5. Incompatible materials

Water. Alcohols. Amines. Acids. Alkalis.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Nitrogen oxides. Isocyanates. Hydrogen cyanide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

LD50 oral rat	2615 mg/kg
---------------	------------

#### Isophorone diisocyanate (4098-71-9)

LD50 oral rat	1097 mg/kg
LD50 dermal rabbit	1060 – 4780 mg/kg
LC50 Inhalation - Rat	0.135 mg/l/4h (mist)

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

These products contain one or more of the following components:

#### Carbon black (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

#### Titanium dioxide (13463-67-7)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified  
Viscosity, kinematic : No data available  
Symptoms/effects : May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Symptoms/effects after skin contact : May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Direct contact with eyes is likely to be irritating.  
Symptoms/effects after ingestion : May cause gastrointestinal irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : No information available.  
Hazardous to the aquatic environment, short-term (acute) : Not classified.  
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT  
Not regulated for transport

#### Transport by sea (IMDG)

Not regulated for transport

#### Air transport (IATA)

Not regulated for transport

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA

SARA Section 311/312 Hazard Classes

Health hazard - Respiratory or skin sensitization

#### 15.2. International regulations

No additional information available

#### 15.3. US State regulations

 **WARNING:** This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

These products contain one or more of the following components:

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Ethylbenzene (100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	
Toluene (108-88-3)		X				7000 µg/day
1,4-Dioxane (123-91-1)	X				30 µg/day	
Carbon black (1333-86-4)	X					
Titanium dioxide (13463-67-7)	X				Not available	
Formaldehyde (50-00-0)	X				40 µg/day	
Tetrachloromethane (56-23-5)	X					
Methyl alcohol (67-56-1)		X				47000 µg/day (inhalation); 23,000 µg/day (oral)
Benzene (71-43-2)	X	X	X		6.4 µg/day (oral); 13 µg/day (inhalation)	24 µg/day (oral); 49 µg/day (inhalation)
Acetaldehyde (75-07-0)	X				90 (inhalation)	
Ethylene oxide (75-21-8)	X	X	X	X	2 µg/day	
Propylene oxide (75-56-9)	X					
1-Methyl-2-pyrrolidone (872-50-4)		X				3200 µg/day inhalation
Naphthalene (91-20-3)	X				5.8 µg/day	
Cumene (98-82-8)	X					

Component	State or local regulations
Isophorone diisocyanate (4098-71-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Ethylbenzene (100-41-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Maleic anhydride (108-31-6)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Toluene (108-88-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
1,4-Dioxane (123-91-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)


## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> ) (1309-37-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Carbon black (1333-86-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Titanium dioxide (13463-67-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Formaldehyde (50-00-0)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Tetrachloromethane (56-23-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Methyl alcohol (67-56-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Massachusetts - Right To Know List
Benzene (71-43-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Acetaldehyde (75-07-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Cumene (98-82-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Propylene oxide (75-56-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Naphthalene (91-20-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Benzene, 1,2,4-trimethyl- (95-63-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Ethylene oxide (75-21-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Dibutyltin dilaurate (77-58-7)	U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - New Jersey - Right to Know Hazardous Substance List
1-Methyl-2-pyrrolidone (872-50-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List

### SECTION 16: Other information

Revision date : 04/04/2023  
 Other information : Author: JMM.  
 NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.  
 NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.  
 NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



# Elasto-Deck 6500 Component A (White); Elasto-Deck 6500 Component A (Concrete Grey)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

### HMIS Hazard Rating

Health	: 2*
	* - Chronic (long-term) health effects may result from repeated overexposure
Flammability	: 1
Physical	: 1

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*