



ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 08/19/2021

Revision date: 08/15/2024

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : ELAST-DECK BT DG

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Waterproofing membrane

1.3. Supplier

Holcim Solutions and Products US, LLC
26 Century Boulevard, Suite 205
Nashville, Tennessee 37214
1-800-878-7876 • www.holcimpacpoly.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency
Spill, Leak, Fire, Exposure, or Incident
CHEMTREC:
Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

| | |
|--|------|
| Flammable liquids, Category 3 | H226 |
| Respiratory sensitization, Category 1 | H334 |
| Skin sensitization, Category 1 | H317 |
| Mutagenicity, Category 2 | H341 |
| Carcinogenicity, Category 1B | H350 |
| Reproductive toxicity, Category 1B | H360 |
| Specific target organ toxicity - Repeated exposure, Category, Category 1 | H372 |
| Hazardous to the aquatic environment - Chronic Hazard, Category3 | H412 |

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H226 - Flammable liquid and vapor.
H317 - May cause an allergic skin reaction.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341 - Suspected of causing genetic defects.
H350 - May cause cancer.
H360 - May damage fertility or the unborn child.
H372 - Causes damage to organs through prolonged or repeated exposure.
H412-Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash clothing, hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.

ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, chemical goggles, & face protection
P284 - In case of inadequate ventilation, wear respiratory protection.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P341 - IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P342+P311 - If experiencing respiratory symptoms: Call a poison center or doctor.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | *% |
|--|----------------------|---------|
| Extracts, petroleum, light paraffinic distillate solvent | (CAS-No.) 64742-05-8 | 20 – 50 |
| Carbon black | (CAS-No.) 1333-86-4 | 7 – 13 |
| Solvent naphtha, petroleum, medium aliphatic | (CAS-No.) 64742-88-7 | 1 – 5 |
| Benzene, 1-chloro-4-(trifluoromethyl)- | (CAS-No.) 98-56-6 | 1 – 5 |
| Petroleum distillates, hydrotreated light | (CAS-No.) 64742-47-8 | 1 – 5 |
| Dibutyltin dilaurate | (CAS-No.) 77-58-7 | 0.1 – 1 |
| Benzene, 1,3-diisocyanatomethyl- | (CAS-No.) 26471-62-5 | 0.1 – 1 |
| Phenol, 4-nonyl-, branched | (CAS-No.) 84852-15-3 | 0.1 – 1 |
| Benzenesulfonyl isocyanate, 4-methyl- | (CAS-No.) 4083-64-1 | 0.1 – 1 |

* In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention immediately.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|------------------------------------|---|
| Symptoms/effects after eye contact | : May cause eye irritation. |
| Symptoms/effects after ingestion | : May cause gastrointestinal irritation. |
| Chronic symptoms | : Suspected of causing genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure. |

4.3. Immediate medical attention and special treatment, if necessary

No additional information available.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | : Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : If water is used, use very large quantities of cold water. The reaction between water and hot isocyanate may be vigorous. |

5.2. Specific hazards arising from the chemical

| | |
|------------------|-----------------------------|
| Fire hazard | : No data available. |
| Explosion hazard | : No data available. |
| Reactivity | : Reacts slowly with water. |

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|--|
| Precautionary measures fire | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| Firefighting instructions | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus. |
| Other information | : Under fire conditions closed containers may rupture or explode. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|--|
| General measures | : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. |
|------------------|--|

6.1.1. For non-emergency personnel

| | |
|----------------------|--|
| Protective equipment | : Wear Protective equipment as described in Section 8. |
| Emergency procedures | : Evacuate unnecessary personnel. |

6.1.2. For emergency responders

| | |
|----------------------|---|
| Protective equipment | : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency. |
|----------------------|---|

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|--|
| For containment | : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. |
| Methods for cleaning up | : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This material and its container must be disposed of in a safe way, and as per local legislation. |

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-------------------------------|---|
| Precautions for safe handling | : Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety procedures. Do not get in eyes, on skin, or on clothing. Avoid breathing vapors, mist. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. |
|-------------------------------|---|

7.2. Conditions for safe storage, including any incompatibilities

| | |
|---------------------------|--|
| Technical measures | : Empty containers retain product residue and can be hazardous. |
| Storage conditions | : Store in a dry, cool and well-ventilated place. Keep the container tightly closed. |
| Heat and ignition sources | : Avoid ignition sources. |

ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Special rules on packaging

: Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Carbon black (1333-86-4) | | |
|--|--------------------------------|--|
| ACGIH | ACGIH OEL TWA | 3 mg/m ³ |
| ACGIH | Remark (ACGIH) | Bronchitis |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL TWA [1] | 3.5 mg/m ³ |
| OSHA | Regulatory reference (US-OSHA) | OSHA |
| Solvent naphtha, petroleum, medium aliphatic (64742-88-7) | | |
| ACGIH | Remark (ACGIH) | OELs not established |
| OSHA | Remark (OSHA) | OELs not established |
| Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) | | |
| ACGIH | Remark (ACGIH) | OELs not established |
| OSHA | Remark (OSHA) | OELs not established |
| Dibutyltin dilaurate (77-58-7) | | |
| ACGIH | Remark (ACGIH) | OELs not established |
| OSHA | Remark (OSHA) | OELs not established |
| Extracts, petroleum, light paraffinic distillate solvent (64742-05-8) | | |
| ACGIH | Remark (ACGIH) | OELs not established |
| OSHA | Remark (OSHA) | OELs not established |
| Petroleum distillates, hydrotreated light (64742-47-8) | | |
| ACGIH | Remark (ACGIH) | OELs not established |
| OSHA | Remark (OSHA) | OELs not established |
| Benzene, 1,3-diisocyanatomethyl- (26471-62-5) | | |
| ACGIH | ACGIH OEL TWA [ppm] | 0.001 ppm inhalable fraction and vapor |
| ACGIH | ACGIH OEL STEL [ppm] | 0.005 ppm inhalable fraction and vapor |
| OSHA | Remark (OSHA) | OELs not established |
| Phenol, 4-nonyl-, branched (84852-15-3) | | |
| ACGIH | Remark (ACGIH) | OELs not established |
| OSHA | Remark (OSHA) | OELs not established |
| Benzenesulfonyl isocyanate, 4-methyl- (4083-64-1) | | |
| ACGIH | Remark (ACGIH) | OELs not established |
| OSHA | Remark (OSHA) | OELs not established |

8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Wear chemically impervious apron over labcoat and full coverage clothing. Respiratory protection of the dependent type.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Nitrile, rubber, or Neoprene. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection:

Lab coat with chemically impervious apron.

Respiratory protection:

An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Liquid |
| Appearance | : Liquid |
| Color | : Black |
| Odor | : Mild aromatic |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : 48.89 °C (120 °F) (Pensky-Martens Closed Cup) |
| Relative evaporation rate (n-butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : > 1 (air = 1) |
| Relative density | : No data available |
| Density | : 7.7 lb/gal ± 0.3 lb/gal |
| Solubility | : Reacts slowly with water |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive limits | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

VOC content : 72 g/l (EPA Method 24)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts slowly with water.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

High temperatures, incompatible materials.

10.5. Incompatible materials

Acids. Alcohols. Alkalis. Amines.

10.6. Hazardous decomposition products

Can be released in case of fire: carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen cyanide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Carbon black (1333-86-4)

LD50 oral rat > 15400 mg/kg

LD50 dermal rabbit > 3 g/kg

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

LD50 oral rat > 5000 mg/kg

LD50 dermal rabbit 3000 mg/kg

LC50 Inhalation - Rat > 5.28 mg/l/4h

Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6)

LD50 oral rat 13 g/kg

LD50 dermal rabbit > 2 ml/kg

LC50 Inhalation - Rat 33 mg/l/4h

Dibutyltin dilaurate (77-58-7)

LD50 oral rat 45 mg/kg

LD50 dermal rabbit 630 mg/kg

Extracts, petroleum, light paraffinic distillate solvent (64742-05-8)

LD50 oral rat > 5000 mg/kg Source: IUCLID

Petroleum distillates, hydrotreated light (64742-47-8)

LD50 oral rat > 5000 mg/kg

LD50 dermal rabbit > 2000 mg/kg

LC50 Inhalation - Rat > 5.2 mg/l/4h

Benzene, 1,3-diisocyanatomethyl- (26471-62-5)

LD50 oral rat 3060 mg/kg

LD50 dermal rabbit 10000 mg/kg

LC50 Inhalation - Rat 0.099 mg/l/4h dust and mist

Phenol, 4-nonyl-, branched (84852-15-3)

LD50 oral rat 1300 mg/kg

LD50 dermal rabbit 2031 mg/kg

Benzenesulfonyl isocyanate, 4-methyl- (4083-64-1)

LD50 oral rat 2234 mg/kg

ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Benzenesulfonyl isocyanate, 4-methyl- (4083-64-1) | |
|--|---|
| LC50 Inhalation - Rat [ppm] | > 640 ppm/1h |
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitisation | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Suspected of causing genetic defects. |
| Carcinogenicity | : May cause cancer. |
| Carbon black (1333-86-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| Benzene, 1,3-diisocyanatomethyl- (26471-62-5) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | Reasonably anticipated to be Human Carcinogen |
| Reproductive toxicity | : May damage fertility or the unborn child. |
| STOT-single exposure | : Not classified |
| STOT-repeated exposure | : Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not classified |
| Viscosity, kinematic | : No data available |
| Symptoms/effects | : May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. |
| Symptoms/effects after inhalation | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Symptoms/effects after skin contact | : May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : May cause eye irritation. |
| Symptoms/effects after ingestion | : May cause gastrointestinal irritation. |
| Chronic symptoms | : Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|--|
| Ecology - general | : No information available. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Harmful to aquatic life with long-lasting effects. |

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

| | |
|-----------------------|----------------------|
| Other adverse effects | : No data available. |
|-----------------------|----------------------|

SECTION 13: Disposal considerations

13.1. Disposal methods

| | |
|--|--|
| Waste treatment methods | : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants. Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit. |
| Product/Packaging disposal recommendations | : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment. |

ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN1263 Paint (Contains: Extracts, petroleum, light paraffinic distillate solvent), 3, III
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint
Contains: Extracts, petroleum, light paraffinic distillate solvent
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a
passenger vessel.
Emergency Response Guide (ERG) Number : 128
Other information : No supplementary information available.

Transport by sea (IMDG)

Transport document description (IMDG) : UN 1263 PAINT (Contains: Extracts, petroleum, light paraffinic distillate solvent), 3, III
UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : PAINT
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L

Air transport (IATA)

Transport document description (IATA) : UN 1263 Paint (Contains: Extracts, petroleum, light paraffinic distillate solvent), 3, III
UN-No. (IATA) : 1263
Proper Shipping Name (IATA) : Paint
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

ELASTO-DECK BT DG

All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA

SARA Section 311/312 Hazard Classes

Physical hazard - Flammable (gases, aerosols, liquids, or solids)
Health hazard - Respiratory or skin sensitization
Health hazard - Germ cell mutagenicity
Health hazard - Carcinogenicity
Health hazard - Specific target organ toxicity (single or repeated exposure)

15.2. International regulations

No additional information available

ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

⚠ WARNING: This product can expose you to Carbon black, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Component | Carcinogenicity | Developmental toxicity | Reproductive toxicity male | Reproductive toxicity female | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
|--|-----------------|------------------------|----------------------------|------------------------------|--|-------------------------------------|
| Toluene (108-88-3) | | X | | | | 7000 µg/day |
| Carbon black (1333-86-4) | X | | | | | |
| Naphthalene (91-20-3) | X | | | | 5.8 µg/day | |
| Ethylbenzene (100-41-4) | X | | | | 54 µg/day (inhalation); 41 µg/day (oral) | |
| Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) | X | | | | | |
| Silica: Crystalline, quartz (14808-60-7) | X | | | | | |
| Benzene, 1,3-diisocyanatomethyl- (26471-62-5) | X | | | | | |

| Component | State or local regulations |
|---|---|
| Toluene (108-88-3) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| Carbon black (1333-86-4) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances |
| Ethylbenzene (100-41-4) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| Silica, amorphous (7631-86-9) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Naphthalene (91-20-3) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| Solvent naphtha, petroleum, medium aliphatic (64742-88-7) | U.S. - New Jersey - Right to Know Hazardous Substance List |
| Carbonic acid, magnesium salt (1:1) (546-93-0) | U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Dibutyltin dilaurate (77-58-7) | U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - New Jersey - Right to Know Hazardous Substance List |
| Silica: Crystalline, quartz (14808-60-7) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| Limestone (1317-65-3) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Benzene, 1,3-diisocyanatomethyl- (26471-62-5) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |
| Isobutane (75-28-5) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Benzoyl chloride (98-88-4) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |


ELASTO-DECK BT DG

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

| | |
|--------------------|--|
| Revision date | : 08/15/2024 |
| Other information | : Author: JMM. |
| NFPA health hazard | : 3 - Materials that, under emergency conditions, can cause serious or permanent injury. |
| NFPA fire hazard | : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. |
| NFPA reactivity | : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures. |
| HMIS Hazard Rating | |
| Health | : 3* |
| Flammability | : 2 |
| Physical | : 1 |



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.