



Color Chart



CONCRETE GRAY*



TAN*



ALOHA BROWN



ALUMINUM GRAY



BAJA BROWN



BRONZE



DESERT SAND



DRIFTWOOD



FALCON GRAY



FLINT GRAY



FOREST GREEN



GRANITE BROWN



LIMESTONE



PUMICE




RELISH



SADDLE



SMOKE GRAY




WHITE



WILSON BLUE



WINGTIP GRAY



OYSTER



PEWTER



SHALE



ADOBE

The actual colors of Elasto-Glaze 6001ALHT Top Coat may vary slightly from the colors shown on the chart. This guide offers a representation of color. When matching is critical, a cured or applied color sample is highly recommended. Color matching available upon request.

* Stock colors are Concrete Gray and Tan. Additional colors and custom colors are achieved with the Elasto-Glaze 6001ALHT Neutral Base and a Color-Pak of the desired color.



ELASTO-POXY PRIMER (VOC)	A two component, solvent based VOC compliant epoxy resin based primer for use with the Elasto-Deck 5000, Elasto-Deck 6500 and Elasto-Deck BT Systems. Also used for re-coats, plywood, concrete and metal substrates.
ELASTO-POXY PRIMER W.B.	Low odor, two component water based epoxy primer for use with Elasto-Deck 5000 polyurethane based deck coating systems and Elasto-Deck 6500 traffic coating systems.
DECK-THANE PRIMER	Single component, moisture-cured, solvent-borne, polyurethane primer for concrete and wood surfaces.
ELASTO-DECK 5001NG	A non-gassing, liquid applied, single component, aromatic moisture-cured polyurethane membrane.
ELASTO-DECK 5001HT	Liquid applied, single component, moisture-cured polyurethane, high tensile polyurethane membrane. For pedestrian, vehicular and under-tile system applications.
ELASTO-GLAZE 6001ALHT	A liquid applied, moisture-cured, polyurethane waterproofing top coat sealer, based on Aliphatic Isocyanates in combination with additives and pigments.
ELASTO-DECK 6500	Two component, aliphatic, high solids, low odor elastomeric traffic coating membrane for pedestrian or vehicular traffic.
ELASTO-DECK BT	Black, modified, liquid applied single component, moisture-cured polyurethane waterproofing coating, designed to form a seamless, flexible rubber membrane impervious to moisture.
ELASTO-DECK BT H2O	Unique, water-cured liquid applied modified polyurethane membrane for “one day” horizontal applications.
ELASTO-MAT D&G	A modified polyurethane waterproofing membrane that can be applied to damp or green concrete.
PERMATHANE® SM7120 PU	A multi-purpose, single component, gun-grade, non-sag, moisture-cured polyurethane sealant.
ELASTO-THANE 200	Two-part, cold applied, self-leveling jet fuel resistant polyurethane joint sealant which cures to a soft, flexible tear-resistant rubber and conforms to Federal Specification SS-S-200E.
ERSYSTEMS® QUICKET	Multi-component, high solid, polyurethane elastomeric binder adhesive system used for correcting slope and ponding issues on deck or roofing applications.